



## Copperloy Lift Tables



### Lift Tables

Copperloy lift tables can accommodate net capacities from 2,500 to 25,000 pounds. They feature vertical lift ranges of 24", 36", or 48" for 2,500 to 6,000 pound tables and 24", 36", 48", and 60" for 8,000 to 25,000 pound tables. All tables are engineered and manufactured in accordance with ANSI MH29.1. Standard platform sizes range from 24" x 36" to 48" x 96". Please consult factory for special sizes.



### Lift and Tilt Tables

We also offer Lift and Tilt Tables, or just Tilt Tables with net capacities between 2,000 and 10,000 pounds. The Lift and Tilt Tables offer a vertical travel of 24", 36" or 48" with a lowered height of 15". Lift and Tilt tables are available in 30°, 45° and 60° of tilt and 90° on our Up-Ender tables. Standard platform sizes range from 24" x 36" to 48" x 64". Please consult factory for special sizes.



### Low-Entry Lift Tables

Our Low-Entry Lift Tables have a net capacity range from 2,500 to 6,000 pounds and a vertical travel of 33", 48" and 60". These tables lower as much as 3/8" from the floor level for easy on/off loading and unloading; eliminating the need for ramps, pits and fork lifts. Standard sizes range from 40" x 48" to 76" x 55". Consult factory for special sizes.

### Double-Long Lift Tables

When lifting and feeding long heavy loads, it is essential that each table top rise simultaneously. This is especially true when lifting loads that are hard to handle. Our Double-Long Lift Tables are ideal for handling material such as pipe, bar stock or lumber. They are especially suited for bundling or banding of materials and can be adjusted for both high or low entry.

#### Options Available

##### Manual Rotating Tops

**Toe Guards**—Sloped side platforms minimize toe and foot injuries. Add 10" to platform top width and length.

**Casters**— Provide easy mobility as well as increasing platform height.

**Accordion Skirt**— Protect employees by restricting unintentional access to the scissor mechanism as well as keeping mechanism free from dirt and chips.

**Conveyors**— Both Gravity and Power Rollers available.

##### High Cycle Packages

**Side rails**— Add additional safety and protection.

#### Standard Items

\*460—Volt, three phase, 2 horsepower motors standard.

\*Single phase, air motors and battery operated units are also available.

\*DU Bearings lubricated for life.

\*Captured upper and lower rollers to prevent upending.

\*Two year warranty on cylinder seals.

All units come painted gray. Other paints are available.

**Safety Bars**— Maintenance safety bars prevent platforms from lowering beyond predetermined levels.

**Standard Controls**— Hand held push button. Foot pedal also available.

**Note**— Lift tables are not intended for lifting personnel unless specifically noted. Overloaded capacities can damage equipment. Tables are intended for balanced loads —not exceeding 50% of capacity on either side of the ends of the table.