



# Aluminum Van Ramp / Walkboard Specifications

## Aluminum Van Ramps

Overall Width	Length	Capacity	Weight	Height Range	Model Number
38 1/2"	6'	4,000	97	0 – 16"	XA40-38-06
	8'	4,000	129	0 – 22"	XA40-38-08
	10'	4,000	161	0 – 28"	XA40-38-10
	12'	4,000	194	0 – 35"	XA40-38-12
	14'	3,500	226	0 – 41"	XA35-38-14
	16'	3,000	258	0 – 48"	XA30-38-16
44 1/2"	6'	2,500	109	0 – 16"	XA25-44-06
	8'	2,500	144	0 – 22"	XA25-44-08
	10'	2,500	180	0 – 28"	XA25-44-10
	12'	2,500	217	0 – 35"	XA25-44-12
	14'	2,500	253	0 – 41"	XA25-44-14
	16'	2,500	289	0 – 48"	XA25-44-16

**Standard Features:**

- 12" Lip
- 4 3/4" Overall curb height
- 15° Grade angles

## Twin Lock Ramp Specifications

### Light Duty

Locked Width	Single Width	Capacity	Length	Height Range	Weight /Pair	Model Number
38"	19"	6,000	10'	20" – 28"	132	LTL6-38-10
			12'	25" – 34"	158	LTL6-38-12
			14'	29" – 40"	184	LTL6-38-14

### Heavy Duty

Locked Width	Single Width	Capacity	Length	Height Range	Weight /Pair	Model Number
38"	19"	7,500	10'	20" – 28"	250	HTL7.5-38-10
			12'	25" – 34"	300	HTL7.5-38-12
			14'	29" – 40"	344	HTL7.5-38-14

**Standard Features:**

- 12" Lip
- 2" Maximum deflection under rated load
- 15° Grade angles
- 3 1/8" Curb height



## Aluminum Walkboard Specifications

### Regular Duty (3-1/4" Curbs)

Width*	Capacity	Length	Height Range	Weight	Model Number
37"	1,500	6'	0 – 22"	67	XA15-37-06
	1,500	8'	0 – 30"	88	XA15-37-08
	1,500	10'	0 – 38"	108	XA15-37-10
	1,500	12'	0 – 46"	128	XA15-37-12
	1,200	14'	0 – 54"	148	XA12-37-14
	900	16'	0 – 62"	169	XA09-37-16
30"	1,500	6'	0 – 22"	58	XA15-30-06
	1,500	8'	0 – 30"	75	XA15-30-08
	1,500	10'	0 – 38"	93	XA15-30-10
	1,500	12'	0 – 46"	110	XA15-30-12
	1,200	14'	0 – 54"	128	XA12-30-14
	900	16'	0 – 62"	145	XA09-30-16
26 1/2"	1,500	6'	0 – 22"	53	XA15-27-06
	1,500	8'	0 – 30"	69	XA15-27-08
	1,500	10'	0 – 38"	85	XA15-27-10
	1,500	12'	0 – 46"	101	XA15-27-12
	1,200	14'	0 – 54"	117	XA12-27-14
	900	16'	0 – 62"	133	XA09-27-16

\*Subtract 2" for usable width

#### Standard Features:

- 20° Grade angle
- 12" Lip (Optional hooks)
- Optional chains



## Aluminum Walkboard Specifications

### Light Duty (2-3/16" Curbs)

Width*	Capacity	Length	Height Range	Weight	Model Number
34"	1,000	4'	0 – 12"	38	XA10-34-04
	1,000	5'	0 – 16"	49	XA10-34-05
	1,000	6'	0 – 20"	56	XA10-34-06
	1,000	7'	0 – 24"	63	XA10-34-07
	1,000	8'	0 – 28"	71	XA10-34-08
	900	9'	0 – 32"	78	XA09-34-09
	800	10'	0 – 37"	85	XA08-34-10
	700	11'	0 – 41"	92	XA07-34-11
	600	12'	0 – 45"	99	XA06-34-12
30"	1,000	4'	0 – 12"	32	XA10-30-04
	1,000	5'	0 – 16"	44	XA10-30-05
	1,000	6'	0 – 20"	51	XA10-30-06
	1,000	7'	0 – 24"	57	XA10-30-07
	1,000	8'	0 – 28"	64	XA10-30-08
	900	9'	0 – 32"	70	XA09-30-09
	800	10'	0 – 37"	77	XA08-30-10
	700	11'	0 – 41"	83	XA07-30-11
	600	12'	0 – 45"	90	XA06-30-12
26 1/2"	1,000	4'	0 – 12"	29	XA10-26-04
	1,000	5'	0 – 16"	40	XA10-26-05
	1,000	6'	0 – 20"	45	XA10-26-06
	1,000	7'	0 – 24"	51	XA10-26-07
	1,000	8'	0 – 28"	57	XA10-26-08
	900	9'	0 – 32"	63	XA09-26-09
	800	10'	0 – 37"	69	XA08-26-10
	700	11'	0 – 41"	75	XA07-26-11
	600	12'	0 – 45"	81	XA06-26-12

\*Subtract 2" for usable width

#### Standard Features:

- 20° Grade angle
- 12" Lip (Optional hooks)
- Optional chains